



# Cleanflex Easy PRO

The Cleanflex Easy PRO ionising air gun can be used for cleaning and neutralising surfaces.

It's unique features, not seen in any other ionising guns, make it very versatile to use.

Ergonomic, hand or pull down, less air consumption, low noise, better blow-off force, take a closer look at all features.

## Features


- + 24V DC input voltage and integrated ionisation power unit**  
The Cleanflex Easy PRO has a 24V input voltage, easily connect by a standardised M12 connector. No cumbersome high voltage cable and big transformer unit as seen in traditional ionisation guns.
- + Lightweight**  
A Durable plastic housing and a well-constructed weight distribution make it a well balanced comfortable gun to use.
- + Ergonomic design**  
The grip has been designed to suit women's as well as man's hands and has a soft grip and grip fixation making it very easy to hold without any muscle tension.
- + Full hand trigger (no RSI strain on one finger)**  
The air flow is controlled with a full hand trigger, making operation very comfortable. No strain on one finger as in traditional ionisation guns.
- + Coiled Hose optional**  
As coiled air hose with integrated 24V cable can be used for operations that have to cover a larger area. The coil expands and retracts with the movement of the operator, reducing tripping hazards.
- + IQS-standard quick connect 8 mm hose**  
A standard 8 mm diameter air hose can be used and quickly connected to the gun without the use of tools. No hose clamps, minimising possible injuries.



- + 70° adjustable nozzle angle**  
The air flow nozzle can be set to 4 positions covering a range of 70°, making it possible to set the flow in the optimal direction for obtaining the best cleaning results and creating an ergonomic condition for the operator.
- + Safe blow-off nozzle opening**  
The nozzle opening has been constructed as a ring making it impossible to block the complete air stream when the tip accidentally touches body parts and preventing injuries due to too high air pressure. (Conform OSHA regulations)
- + Low Noise and Reduced air consumption and improved blow-off force**  
A special nozzle opening design, making use of air amplification principles, enables the CleanFlex Easy to produce a very compact air stream, with low noise, reduced air consumption and improved blow-off force compared to other anti static guns.
- + Ion balance**  
The Cleanflex Easy PRO has an ion balance of +/- 30 V for use in blow cleaning plastic products that contain ESD sensitive electronics.

Comparison with Simco anti-static guns (all details are @ 2 bar):

CleanFlex Easy PRO	Cobra	ES-2J
compared to		
Air consumption	-45%	-40%
Blow-off force	2,55 x more	1,2 x more
Noise level	- 15dB (5 times less)	- 3dB (2 times less)



### Multi application

#### + Hand and pull down

As well as conventional hand use, the Cleanflex Easy PRO can also be mounted upside down with a balancer. The grip and air trigger can be held and operated in both situations.

#### + Durable hanging positions

At two positions, durable metal hanging openings are provided.

#### + LED indicator

The multi colored LED is at a good visible location and provides information about the operation state of the Cleanflex Easy PRO. Green, slow flashing, indicates that the gun has power and is ready for operation. (still alive mode)

Green, high brightness, continuous on, indicates that the trigger has been activated and enough air pressure is applied to be in operation.

Red, a fault is detected, the ionisation is switched off.

#### + Automatic ionisation on/off

The ionisation is only switched on when the trigger is active and enough air pressure has been measured by an internal sensor. This provides safety , low energy usage and extends ionisation emitter life.

#### + No silicone

The Cleanflex Easy PRO is constructed with materials and component that do not contain silicone. Also in the production process no materials with silicone are used, making the ionisation gun suitable for painting applications.



LED indication



Soft grip




## Technical specifications

Power supply	24 V DC, max. 0,3 A
Connector	M12, female, 5 pole
Ion balance	+/- 30V
Pinning	1: 24 V DC, 2: HV OK, 3: 0 V/GND, 4: 24 V DC, 5: Not connected
Compressed air	1-7 bar, clean and free from oil
Connection	Quick disconnect type for ø8 mm hose
LED indicator	Flashing green fast (5 Hz): Starting up Flashing green slow (1 x every 3 seconds): Stand-by (ready for operation) Continuous green: Air pressure OK and HV ON (normal operation) Red: Failure check wiring or contact Simco ION



Easy Power Lite: 110-230V (EU)



Desktop 110-230V (NON EU)

### Simco-Ion Netherlands

P.O. Box 71  
Lochem, The Netherlands NL-7240 AB  
Tel: +31 (0)573 288333  
Fax: +31 (0)573 257319  
general@simco-ion.nl  
www.simco-ion.nl